

COACHMAN® collection



Coachman® Collection Design 12 with REC13 Window Design

HANDCRAFTED 4-LAYER CONSTRUCTION

- 1 COMPOSITE OVERLAY
- 2 STEEL
- 3 POLYURETHANE INSULATION
- 3 POLYSTYRENE INSULATION
- 4 STEEL



The Coachman® Collection gives your home classic elegance while complementing your home's architectural style. It's the perfect blend of beauty and practicality—masterful in details and innovative in design.

STYLE AND CONSTRUCTION

- Custom composite overlay with beveled coped edge and center groove creates a detailed carriage house look.
- Windows with complete overlay and true arch designs are available in double strength, Insulated or Obscure glass. Grilles are removable for ease of cleaning.
- Model CD has 1-3/8" thick polystyrene (R-value 6.5).
- Model CG has 2" thick polystyrene (R-value 9.0).
- Model CGU has 2" thick polyurethane (R-value 17.2).
- Insulated with a thermal break, sandwiched between two layers of bonded steel.

Calculated door section R-value is in accordance with DASMA TDS-163.

COACHMAN® DOOR DESIGNS

COACHMAN® DOOR DESIGNS					
SERIES 1			SERIES 2		
Design 11 with REC11 Window*	Design 12 with SQ24 Window*	Design 13 with REC13 Window*	Design 21 with ARCH4 Window*	Design 22 with REC14 Window*	Design 23 with ARCH3 Window*
SERIES 3**					
Design 31	Design 32	Design 33	Design 34	Design 35	Design 36
SERIES 4**			Available in 4 carriage house design series and 15 different models. Custom designs and sizes also available. *Various window designs may be chosen with each door design. Examples are shown. **Series 3 and 4 are not available with windows.		
Design 41	Design 42	Design 43			

WINDCODE® AVAILABILITY CHART

Common Door Widths		W1	W3	W4	W5	W6	W7	W8
Model CD	8', 9' Wide Door	S +13/-15 PSF	SELECT W5	SELECT W5	FTS +33/-37 PSF			
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS +25/-25 PSF				
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS +25/-25 PSF				
	18' Wide Door	S +12.5/-14 PSF						
Models CG/CGU*	8', 9' Wide Door	SELECT W6	SELECT W6	SELECT W6	SELECT W6	FT*S +38/-42 PSF	SELECT W8	FT*D* +54/-60 PSF
	10', 12' Wide Door	SELECT W5	SELECT W5	SELECT W5	FT*S +30/-30 PSF	FT* +37.5/-40 PSF	SELECT W8	FD* +46.6/-52 PSF
	16' Wide Door	SELECT W5	SELECT W5	SELECT W5	FT*S +30/-30 PSF	FT* +37.5/-40 PSF	SELECT W8	FD* +46.6/-52 PSF
	18' Wide Door	SELECT W6	SELECT W6	SELECT W6	SELECT W6	FT* +37/-37 PSF		

COLORS

	White
	Almond
	Desert Tan
	Sandtone

(Note: Overlay color and base color can be mixed and matched.)

S Standard Windows Available
I Impact Rated

W Impact Windows Available
F Florida Approved

D Dade County Approved
T Texas Department of Insurance Approved

For W6-W8 doors over 9' wide, add 2" to the door opening.

*Model CGU is not Texas or Dade approved.